



Henshaws Roofing and **Building Supplies** Thomas Street Stretford Manchester M32 0JT **Tel:** 0161 865 8899

Henshaws Roofing and **Building Supplies** 160 Higher Road Urmston Manchester M41 5TU


**Tel:** 0161 748 8927



### RollRidge - Dry Fix Ridge system

RollRidge provides a no maintenance alternative to a wet bedded ridge. It also offers high level ventilation.


For use with 457 mm Duracoat legged angle ridges and 305mm clay half round ridges.



#### Koraflex

Is a flashing system for weatherproofing roof junctions such as side and top abutments around chimneys and dormers.

Available in two widths 320mm and 450mm and three standard colours grey, red and black.



# Roll Hip - Dry Fix Hip system

Roll Hip provides a no maintenance alternative to a wet bedded hip.

For use with 457 mm Duracoat Segmental or legged angle hip tiles and 305mm clay third round ridges.


Sandtoft RoofSPEC® home gives you:

- 10 year weathertight roof guarantee
- No maintenance peace of mind
- Assurance with Sandtoft roof tiles guarantees
- Henshaws selected contractors
- Complete package - includes products, fixing and specification

RoofSPEC® home

**Sandtoft** 

10 YEAR
WEATHERTIGHT
GUARANTEE





Designed to ventilate the roof, support the insulation and underlay. Eliminates the problem of underlay deterioration at the eaves and provides effective resistance to large insects and driving rain.



#### Dry Verge systems

Three systems are available. LF, MF and Multiverge dry verge systems are all colour matched to complement the tiles and slates and are easy to fix, providing a neat, secure and mortarless finish at roof verges.

# Clay Cloaked Verge

A new system is available in clay, suitable for use at both left and right hand verges.



Sandtoft Classic Vapour permeable membrane

Suitable for both warm and cold roof designs on any roof shape and building type.

### Rollvent

The Sandtoft Rollvent top abutment ventilation system provides a neat and discreet way of ventilating the roof space at a top abutment.